MATERIAL SAFETY DATA SHEET

INTERTHANE 990HS/870HS CONVERTER

Sales Order: {SalesOrd}

MSDS Revision No:

A0 -6

01/19/2002 MSDS Revision Date:

EMERGENCY NUMBERS:

(800) 424-9300

CHEMTREC (USA)

International Paint Inc.

(703) 527-3887

CHEMTREC (Intl)

6001 Antoine Drive

(800) 854-6813

Poison Control Center

CUSTOMER SERVICE:

(Non-Emergency)

(800) 589-1267

International Paint

Houston, Texas 77091

(800) 631-7481

Interlux

1. **GENERAL INFORMATION**

Product Identity:

INTERTHANE 990HS/870HS CONVERTER

Bulk Sales Reference No:

XInternational.

IMPORTANT: Read this MSDS before handling or disposing of this product, and provide this information to the employee, customers, and users of this product. PLEASE NOTE THE MSDS REVISION NUMBER AT THE TOP OF THIS PAGE. If the MSDS Revision Number posted at the top of this page does not match the MSDS Revision Number on the product label, please contact Customer Service at the phone number included above for the greet MSDS. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with actrements of this standard.

2. HAZARDOUS INGREDIENT INFORMATION

~AS No.	Ingredient Name & %	Source	Exposure Data
	Pseudocumene 1.0 - 10% by Weight	OSHA:	No Data Available
		ACGIH:	No Data Available
		NIOSH:	25 ppm TWA; 125 mg/m3 TWA
		Supplier:	No Data Available
		OHSA, CAN:	No Data Available
		Mexico:	No Data Available
000095-63-6		Brazil:	No Data Available
000093-03-0		Source	Health Data
		NIOSH:	No Data Available
		Source	Carcinogen Data
		OSHA:	Select Carcinogen: No
		NTP:	Known Carcinogen: No; Suspected Carcinogen: No
4 10 10 10 10 10 10 10 10 10 10 10 10 10		IARC:	Group 1: No; Group 2A: No;
		IARC:	Group 2b: No; Group 3: No; Group 4: No
CAS No.	Ingredient Name & %	Source	Exposure Data

000123-86-4	n-Butyl acetate 1.0 - 10% by Weight	0.077.4	150 TWA 710/2 TWA 200 CTEL . 050 mg/m2 CTEL
		OSHA:	150 ppm TWA; 710 mg/m3 TWA200 ppm STEL; 950 mg/m3 STEL
		ACGIH:	150 ppm TWA200 ppm STEL 150 ppm TWA; 710 mg/m3 TWA200 ppm STEL; 950 mg/m3 STEL1700
		NIOSH:	ppm IDLH
		Supplier:	No Data Available
		OHSA, CAN:	150 ppm TWAEV; 710 mg/m3 TWAEV200 ppm STEV; 950 mg/m3 STEV
		Mexico:	150 ppm TWA; 710 mg/m3 TWA200 ppm STEL; 950 mg/m3 STEL
		Brazil:	No Data Available
		Source	Health Data
		NIOSH:	Mucous membrane and eye irritation; high concentrations cause nervous system effects in animals
		Source	Carcinogen Data
		OSHA:	Select Carcinogen: No
		NTP:	Known Carcinogen: No; Suspected Carcinogen: No
		IARC:	Group 1: No; Group 2A: No;
			Group 2b: No; Group 3: No; Group 4: No
CAS No.	Ingredient Name & %	Source	Exposure Data
	Hexamethylene diisocyanate homopolymer 75 - 100% by Weight	OSHA:	No Data Available
		ACGIH:	No Data Available
		NIOSH:	No Data Available
		Supplier:	No Data Available
		OHSA, CAN:	No Data Available
		Mexico:	No Data Available
028182-81-2		Brazil:	No Data Available
		Source	Health Data
		NIOSH:	No Data Available
		Source	Carcinogen Data
		OSHA:	Select Carcinogen: No
		NTP:	Known Carcinogen: No; Suspected Carcinogen: No
		IARC:	Group 1: No; Group 2A: No;
			Group 2b: No; Group 3: No; Group 4: No
CAS No.	Ingredient Name & %	Source	Exposure Data
		OSHA:	No Data Available
		ACGIH:	No Data Available
	Petroleum naphtha, light aromatic 1.0 - 10% by Weight	NIOSH:	No Data Available
		Supplier:	No Data Available
		*	No Data Available
		Mexico:	No Data Available
064742-95-6		Brazil:	No Data Available
		Source	Health Data
		NIOSH:	No Data Available
		Source	Carcinogen Data

OSHA:

Select Carcinogen: No

NTP:

Known Carcinogen: No; Suspected Carcinogen: No

Group 2A: No; Group 1: No;

IARC:

Group 3: No; Group 4: No Group 2b: No;

HAZARD IDENTIFICATION 3.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and

nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Avoid contact with eyes, skin and clothing. Contains 1,2,4-Trimethylbenzene which can cause central nervous system

depression, anemia and bronchitis.

May be harmful or fatal if inhaled. May cause lung injury. Causes nose and throat irritation. Vapors may affect the brain or Inhalation:

nervous system causing dizziness, headache or nausea.

Causes severe eye irritation. Avoid contact with eyes. Eyes:

Overview:

Respiratory:

Eyes:

Skin/Hand:

Causes skin irritation. May cause allergic skin reaction. May be harmful if absorbed through the skin. Skin:

Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness. Ingestion:

Contains an ingredient which can cause organ damage (See Section 2 and Section 15 for each ingredient). Cancer hazard. **Chronic Effects:**

Contains an ingredient which can cause cancer (See Section 2 and Section 15 for each ingredient). Risk of cancer depends on

duration and level of exposure.

HMIS Rating: Health: 2 Flammability: 2 Reactivity: 0

4. FIRST AID MEASURES

Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or General:

destroy contaminated shoes.

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical Inhalation:

attention immediately.

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately. يyes:

In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately. Skin:

If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do Ingestion:

so by medical personnel. Never give anything by mouth to an unconscious person.

5. PROTECTIVE EQUIPMENT AND CONTROL MEASURES

Select equipment to provide protection from the ingredients listed in Section 2 of this document, Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY

PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical

Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material

Safety Data Sheet. INDIVIDUALS WITH LUNG OR BREATHING PROBLEMS OR PRIOR REACTION TO

ISOCYANATES MUST NOT BE EXPOSED TO VAPOR OR SPRAY MIST. Do not breathe vapor or spray mist. Wear an appropriate, properly fitted respirator (NIOSH approved) during and after application unless air monitoring demonstrates vapor/mist levels are below applicable limits. A supplied air respirator (either positive pressure or continous flow type) is required. Follow manufacturer's directions for respirator use and observe requirements specified in 29 CFR 1910.134.

Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 2 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and

face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 2 of this

document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be

required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.

Engineering Controls: Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use ther Work Practices: good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing

and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

FIRE AND EXPLOSION INFORMATION 6.

tash Point:

F: 135

C: 57

Lower Explosive Limit (LEL):

.6 (%vol in air) at Normal Atmospheric Temp and Pressure

Combustible liquid and vapor. FLAMMABLE/COMBUSTIBLE MATERIALS: Will be easily ignited by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash

Fire and Explosion Hazards:

back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers,

basements, tanks) creating a vapor explosion hazard. Runoff to sewers may create fire or explosion hazard.

Containers may explode when heated.

CAUTION: This product has a very low flashpoint. Use of water spray when fighting fire may be inefficient. SMALL FIRES: Use dry chemical, CO2, water spray or alcohol-resistant foam. LARGE FIRES: Use water spray, fog, or alcohol-resistant foam. Do not use straight streams. Move containers from fire area if you can do so without risk. Runoff from fire control may cause pollution. Dike fire control water for later disposal. Do not scatter the

Fire Fighting Procedures:

Also Reference Emergency Response Guide Number: 127

7. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:

Liquid

pH:

Not Determined

Specific Gravity:

1.1295

Boiling Point (F):

294

Vapor Density:

Heavier than air

OC Content (lbs):

Refer to the Technical Data Sheet for this product

Evaporation Rate:

Slower than ether

8. STABILITY AND REACTIVITY DATA

General:

This product is stable and hazardous polymerization will not occur.

Incompatible Materials:

Strong oxidizing agents.

Hazardous Decompostion:

May produce hazardous fumes when heated to decomposition as in welding. Fumes may produce Carbon Dioxide and

Carbon Monoxide.

9. HANDLING AND STORAGE

Storage Temperature:

Store between 32 and 120 F

Handling and Storage

Precautions:

Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Vapors may cause flash fire or ignite explosively. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Avoid contact with eyes, skin and clothing. Close container after each use. Wash thoroughly after handling.

10. TOXICOLOGICAL DATA

General:

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. No additional information provided for this product. See Section 2 for chemical specific data.

ECOLOGICAL DATA 11.

∡eneral:

No additional information provided for this product. See Section 2 for chemical specific data.

ACCIDENTAL RELEASE MEASURES 12.

ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only nonsparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if

Spill Response Procedures:

you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to

containers. Use non-sparking tools to collect absorbed material.

CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).

Also, Reference Emergency Response Guide Number: 127

DISPOSAL CONSIDERATION 13.

Waste Disposal:

Public Safety:

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. TRANSPORTATION INFORMATION

PAINT

IMO / IMDG (Ocean Transportation) DOT (Domestic Surface Transportation)

DOT Proper Shipping Name: IMDG Proper Shipping Name:

PAINT

)T Hazard Class:

IMDG Hazard Class: UN 1263

UN Number: UN 1263

3.3 - High flashpoint flammable liquids

DOT Packing Group:

UN / NA Number:

Ш

IMDG Packing Group:

CERCLA/DOT RQ:

3037 gal. / 28571 lbs.

System Reference Code: 1

15. REGULATORY INFORMATION

Regulatory Overview:

The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act)

Inventory or are not required to be listed on the TSCA Inventory.

Hexamethylene diisocyanate: final RQ = 100 pounds (45.4 kg)

Xylenes (o-, m-, p- isomers): final RQ = 100 pounds (45.4 kg)

WHMIS Classification:

B3; D1B

Regulatory List

Product Ingredients on List

Cumene: final RQ = 5000 pounds (2270 kg)

n-Butyl acetate: final RQ = 5000 pounds (2270 kg)

DOT Marine Pollutants (10%):

(No Product Ingredients Listed) DOT Severe Marine Pollutants (1%): (No Product Ingredients Listed)

EPCRA 311/312 Chemicals and RQs:

000098-82-8

000123-86-4

000822-06-0

001330-20-7 **EPCRA 302 Extremely Hazardous:** (No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals:

000098-82-8

200822-06-0

Cumene

000095-63-6 001330-20-7 Hexamethylene diisocyanate

Pseudocumene

Xylenes (o-, m-, p- isomers)

Mass RTK Substances: n-Butyl acetate 000123-86-4 000095-63-6 Pseudocumene Mass Extraordinarily Haz Substances: (No Product Ingredients Listed) enn RTK Substances: 000123-86-4 n-Butyl acetate Pseudocumene 000095-63-6 Penn Special Hazardous Substances: (No Product Ingredients Listed) Rhode Island Hazardous Substances: Cumene 000098-82-8 000123-86-4 n-Butyl acetate 001330-20-7 Xylenes (o-, m-, p- isomers) RCRA Status: (No Product Ingredients Listed) N.J. RTK Substances: n-Butyl acetate 000123-86-4 Pseudocumene 000095-63-6 N.J. Special Hazardous Substances: n-Butyl acetate 000123-86-4 N.J. Env. Hazardous Substances: 000098-82-8 Cumene 000822-06-0 Hexamethylene diisocyanate 000095-63-6 Pseudocumene 001330-20-7 Xylenes (o-, m-, p- isomers)

Proposition 65 - Carcinogens:

(No Product Ingredients Listed)

Proposition 65 - Female Reproductive Toxins:

(No Product Ingredients Listed)

Proposition 65 - Male Reproductive Toxins:

(No Product Ingredients Listed)

Proposition 65 - Developmental Toxins:

(No Product Ingredients Listed)

16. OTHER INFORMATION

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

End Of Document